

DEMAK[®]



TECHINICAL FEATURES

	DP DEGASSING PUMP
EQUIPMENT SIZE	550x640x1120h mm / 22x25x44h in
WORKING TABLE HEIGHT	No Working Bench
ELECTRICAL POWER SUPPLY	208/400 Volt three-phase (+ neutral) + ground 50/60 Hz
ELECTRICAL INPUT	2,5 kW
PNEUMATIC SUPPLY	5 bar ±0.5
AIR CONSUMPTION	Working: 5 lt/min
PUMP OPERATION	Pneumatic
MATERIAL LOADING SYSTEM	Automatic Via vacuum
DEGASSING PUMP	1,5 lt. - Patented Technology
DEGASSING SYSTEM	Continuous
DOSING DISPLAY	Via touch panel
MIXER	Disposable static mixer
DOSING VALVE	Anti-drop
RESIN-CATALYST RATIO	Variable Pre-fixed 1:1
MAX. DOSING SPEED	20 cc/sec
AVERAGE PRODUCTIVITY	2-3 sheets/min
SEALS	PTFE Viton

ACCESSORIES

- No. 1 single head
- No. 3 dispensing heads with 2, 4, 6 nozzles
- No. 6 nozzle holders
- No. 1 case with spare seals and mixers

OPTIONALS

- No. 20 washable platens 350x500 mm / 14x20 in
- Working bench with dust-free room
- Working bench with dust-free room and oven
- Automatic X-Axis



DEMAK AMERICA Inc.

140 Commerce Way - Unit E - Totowa, NJ 07512 (USA)
 Phone no. (+1) 973 237.0919 / 973 237.0920
 Fax no. (+1) 973 237.0926
<http://www.demakamerica.com>
 eMail: demak@demakamerica.com

DEMAK S.r.l.

Strada del Cascinotto, 163 - 10156 Torino (ITALY)
 Phone no. (+39) 011 223.98.76
 Fax no. (+39) 011 223.98.96
<http://www.demak.it>
 eMail: sales@demak.it

DEMAK SOUTH AMERICA Tecnologia Para Resinas Ltda

Avenida Antonio Gazzola, 1001 - Sala 3B, 7° Andar
 Bairro Novo Itu - CEP 13301-916 ITU - SP (Brazil)
 Phone no. (+55) 11 4013.0335
<http://www.demaksouthamerica.com>
 eMail: sales@demaksouthamerica.com